

UKAS UKAS

No. 106

Oakwood House City Road Bradford West Yorkshire BD8 8JY Tel: 01274 760400 Fax: 01274 760418

Sunbaba Screens Sunbaba Systems Ltd Sunbaba House, Dullingham Newmarket, Suffolk CB8 9XA Attn: Trevor Booth

Certificate No. BTX/17508(1)/MJD/01

Date: 8th March 2001

Page 1/1

Your Ref. : Delivery 2/3/01

REPORT ON SAMPLE SUBMITTED ON 2nd March 2001

Black mesh fabric - Sample A

Specification for curtains and drapes (BS5867:Part 2:1980) Flammability requirements: Type B Performance

The sample was tested after water soaking in accordance with BS5651:1978 clause 4.

Requirements:

No part of any hole nor any part of the lowest boundary of any flame shall reach the upper edge or either vertical edge of any specimen, and there shall be no separation of flaming debris.

Conditioning:

The samples were conditioned in an atmosphere having a temperature of 20 \pm 2°C and a relative humidity of 55% to 65%.

Results:

These results may not apply to situations where there is restricted air supply or prolonged exposure to large sources of intense heat as in a conflagration.

Flame application time: 15s	Length			Width		
	1	2	3	1	2	3
Flame reached an edge: Hole reached an edge: Flaming debris:	No No No	No No No	No No No	No No No	No No No	No No No

<u>Comments</u> The fabric tested meets the requirements of BS 5867 Performance code B.

Mark Dawes B.Sc. (Hons), C.Text., A.T.I. Senior Technologist, O Textile Department